



PIERRES & CAILLOUX

Créateur, constructeur de broyeurs et d'andaineurs

S.A.S - 52700 ROCHEFORT-SUR-LA-COTE

☎ Office 03.25.31.78.37 - 🏠 Workshop 03.25.02.93.69

📠 03.25.31.48.63

E mail: pierres-cailloux@wanadoo.fr

Website: www.pierresetcailloux.fr



AGRICULTURAL RANGE

TECHNICAL CHARACTERISTICS

AGRICULTURAL STONE CRUSHER	BP 144	BP 194	BP 244
Number of hammers: twin carbide tips	12	18	24
Working width at input	1 440 mm	1 940 mm	2 440 mm
Crusher input height	310 mm	350 mm	350 mm
Rotor width	1 000 mm	1 500 mm	2 000 mm
Diameter of one-piece rotor with hammers	315 mm	355 mm	355 mm
Rotor speed: min. max.	700 RPM 1 800 RPM	700 RPM 1 600 RPM	700 RPM 1 600 RPM
Forged machined one-piece steel rotor bearings	As standard		
Roller bearing units, triple-sealed with solid bronze cage	As standard		
Dual-action hydraulic rotor cowling	As standard		
Bevel gear power	160 HP	265 HP	265 HP
Number of belts	10 (ref : XPB)	12 (ref : XPB)	12 (ref : XPB)
Tractor power take-off (PTO)	1 000 RPM	1 000 RPM	1 000 RPM
Tractor power: min. max.	70 HP 140 HP	100 HP 200 HP	130 HP 220 HP
HARDOX 500 abrasion-proof shielding, 12 mm thick, on rotor cowling and skids	Option		
Automatic greasing unit	Option		
Crusher dimensions (metres)	1.30 x 1.44 x 1.20	1.40 x 1.94 x 1.30	1.40 x 2.44 x 1.30
Grinder weight in working order	1 444 kg	2 340 kg	2 740 kg

Data given for information only; we reserve the right to modify our models and their equipment and accessories without notice.

Made in France, European Union.